



UMU AD20 B2HSB
Spray gun is not included

UMU A/B - MANUAL REWIND HOSE REELS

UMU A/B models are basic manual rewind hose reels. The hose can be pulled out to the desired length, oriented for release and safely returned into initial position after use. It can be assembled on a mobile cart or fixed to floor, wall or ceiling. Its construction is industrial grade, it's safe for operators, wear-resistant, and leak-free. They are specially designed for swivel nozzles and can be customized in length, materials, operating pressure and temperature to satisfy your requirements.

- Typical applications food factories, washing lines, car wash
- Inlet thread size 1/2", 1"
- Outlet thread size 1/2", 1"
- Flexible hose size 3/8", 1/2", 1"
- Max hose length 70 M
- Max working pressure **LP** 200 bar
- Material Body **B2** AISI 304 Stainless steel

Code	LP bar	E inch	U inch	DI mm	MF inch	LF m	W kg	DE mm	H mm	S mm	Swivel code
UMU BF10 B2LSB	20	1"	1"	20	1"	10	12	500	460	270	on request
UMU BF20 B2LSB					1"	20	13	500	460	340	
UMU AC20 B2HSB	200	1/2"	1/2"	10	3/8"	20	9	390	330	300	
UMU AD20 B2HSB					1/2"	20					
UMU BC50 B2HSB					3/8"	50	12	500	460	270	
UMU BD35 B2HSB					1/2"	35					
UMU BC70 B2HSB					3/8"	70	13	500	460	340	
UMU BD50 B2HSB					1/2"	50					

UMU G / H (AUTO - REWIND HOSE REELS)



UMU HD20 B2HSB

UMU G/H - AUTO-REWIND HOSE REELS

UMU G/H models are auto-rewind hose reels with multi-position release, very useful and practical for frequent cleaning operations. The hose can be easily pulled out from the reel for the desired length and locked in place during use. When washing is completed, a short further pull activates a spring powered automatic rewind mechanism that returns the hose onto the reel. It's suitable for a variety of industrial environments, wear-resistant, robust in construction and designed to mount floor, wall, ceiling or cart.

- Typical applications food factories, washing lines, car wash
- Inlet thread size 1/2", 1"
- Outlet thread size 1/2", 1"
- Flexible hose size 3/8", 1/2", 3/4", 1"
- Max hose length 20 M
- Max working pressure **LP** 200 bar
- Material Body **B2** AISI 304 Stainless steel

Code	LP bar	E inch	U inch	DI mm	MF inch	LF m	W kg	DE mm	H mm	S mm	Swivel code
UMU HE13 B2LSB	20	1"	1"	20	3/4"	13	18	530	550	300	XUM US20 B2
UMU HF08 B2LSB					1"	8	18				
UMU HE18 B2LSB	20	1"	1"	20	3/4"	18	24	530	550	480	XUM US22 B2
UMU HF15 B2LSB					1"	15	24				
UMU GD15 B2HSB	200	1/2"	1/2"	10	1/2"	15	13	550	430	230	XUM US15 B2
UMU GD20 B2HSB					1/2"	20	18	550	430	260	XUM US20 B2
UMU HC20 B2HSB					3/8"	20	18	530	550	300	
UMU HD20 B2HSB					1/2"	20	18	530	550	300	